

SPECPOXY COATING

A 2 component, high performance epoxy coating system designed to provide concrete and steel surfaces with excellent abrasion resistance in combination with protection against chemical attack.

[MSDS/SDS](#)
[Spec Sheet](#)

SPECPOXY C.J.

SPECPOXY C.J. is two component, semi-rigid epoxy for filling control and construction joints in industrial concrete floors. This product supports the joint edges and reduces spalling of the edges caused by wheel traffic. SPECPOXY C.J. is useful for contraction/construction joints that are cut or formed. SPECPOXY C.J. may be used for the repair of damaged or spalled joint nosing and cracks.

[MSDS/SDS Parts A and B](#)
[Spec Sheet](#)

SPECPOXY 3000FS

A two component, moisture insensitive, high modulus, structural epoxy bonding gel. SPECPOXY3000 FS is 100% solids, solvent free, low odor, high strength, and non-sag.

- Anchors bolts, dowels, and reinforcing steel
- Vertical and overhead structural bonding and patching
- Sealing of cracks and the setting of injection ports
- For use in concrete, block, brick, or stone
- VOC Content = 0 grams per liter

[MSDS/SDS](#)
[Spec Sheet](#)



DAYTON SURE INJECT™ J56

Sure Inject™ J56 is a 100% solids, high modulus, moisture tolerant, low viscosity epoxy adhesive for gravity feed or pressure injection of cracks in concrete.

[MSDS Parts A and B](#)
[Spec Sheet](#)