



ARMOR-TILE™ TACTILE SYSTEMS

In test after test, Armor-Tile™ exceeds the most stringent requirements for:

- Wear and slip resistance (aluminum oxide).
- Impact resistance (continuous fiberglass reinforcement).
- Weathering (epoxy based, UV resistant pigments).
- Detectability (sharp color features and sound response to cane contact).

Both Armor-Tile™ tactile warning cast-in-place and surface applied systems are available in 7 standard sizes and 8 standard colors. Great Plains inventories a variety of options with others available on special order.

Cast-in-place:

40-ADAC-2424RD	2'x2' Brick Red Armor-Tile (cast-in-place)
40-ADAC-2436RD	2'x3' Brick Red Armor-Tile (cast-in-place)
40-ADAC-2448RD	2'x4' Brick Red Armor-Tile (cast-in-place)
40-ADAC-2460RD	2'x5' Brick Red Armor-Tile (cast-in-place)
40-ADAC-3648RD	3'x4' Brick Red Armor-Tile (cast-in-place)
40-ADAC-3660RD	3'x5' Brick Red Armor-Tile (cast-in-place)
40-ADAC-2448COL	2'x4' Colonial Red Armor-Tile (cast-in-place)
40-ADAC-2460COL	2'x5' Colonial Red Armor-Tile (cast-in-place)

Surface applied:

40-ADAS-2448RD	2'x4' Brick Red Armor Tile (surface applied)
40-ADAS-2460RD	2'x5' Brick Red Armor Tile (surface applied)

Call [Great Plains](http://www.greatplainsconcrete.com) at 913-385-9121 for assistance in selecting the right tactile warning tile for your project.