





CAM® GAUGE RAKE

A patented "goof-proof" tool which applies a range of materials at a precise, specified, and uniform depth. For use in applying decorative concrete "toppings," self leveling/high performance floor coating materials, and underlayments in the floor-covering markets.

18-57000 24" w/Threaded Handle Adapter (Frame Only) 18-57001 24" w/66" Powder-Coated Aluminum Handle



"FLEXIBLE BED" SPIKED SHOES

Revolutionary - perfect fit, balance and flexibility. Toe and heel guards. Snap-lock buckle system. 1/2" spike length. 20 replaceable spikes per shoe.

18-46140 Size Small (Shoe size 6 to 7-1/2)
18-46141 Size Medium (Shoe size 8 to 9-1/2)
18-46142 Size Large (Shoe size 10 to 11-1/2)
18-46143 Size Extra-Large (Shoe size 12 to 13-1/2)
18-46129 Replacement Spikes (set of 40)



BLACK SPIKED SHOES Durable solvent-resistant polypropylene. Snap-lock buckle system. 13 specially placed spikes per shoe.

18-46112 Black Spiked Shoes (pair)18-46122 3/4" Rounded Tip Replacement Spike (set of 26)

CAM® GAUGE RAKE CAM® SETS

18-57082 Size 2 (1/8") 18-57083 Size 3 (3/16") 18-57084 Size 4 (1/4") 18-57086 Size 6 (3/8") 18-57088 Size 8 (1/2")



SPIKED ROLLERS

Designed to be used on freshly applied floor coatings for the purpose of releasing trapped gas as well as to assist in the leveling process of several varieties of floor coatings.

18-SA10062 9" Head Width Replacement Roller 18-SA10063 18" Head Width Replacement Roller





AND _____

HARDWOOD HANDLES

18-SA20174 66" Handle w/Aluminum Threaded Tip18-SP20220 1-1/8"x60" Hardwood Handle, Tapered Tip18-SP20215 15/16"x60" Hardwood Handle, Metal Threaded Tip

ALUMINUM HANDLES Powder-Coated w/Milled Threaded Tips.

18-SA20174 66" Aluminum Handle