

SPEC CHEM STRONG BOND ACRYLIC BONDER

An admixture and bonding agent designed to improve adhesion and durability of many repair mortars. Improves flexural strength and impact resistance of mortars. Improves freeze-thaw cycle resistance.

21-10450 1-Gal. Jug

Spec Sheet MSDS/SDS

SPECPATCH 15 (Formerly PRECAST PATCH)

A general purpose concrete repair mortar used for horizontal and vertical applications. Provides durable repair for interior and exterior projects. Primary uses:

Curbs.

- Precast concrete.
- Sidewalks.

21-10470 50 lb. Pail 21-10471 50 lb. Bag

Spec Sheet MSDS/SDS

SPEC CHEM DUO PATCH

A two component, polymer modified concrete repair mortar for use in horizontal repair. Provides superior durability. Primary uses:

- Industrial warehouse floors.
- · Parking decks.
- Garage floors.

21-10460 50 lb. Bag and 1 Gal. Jug

Spec Sheet MSDS/SDS

SPEC CHEM REVCRETE - COURSE

A single component, polymer modified concrete repair mortar, ideally suited for resurfacing concrete in need of a light broom finish. The blend of fine and course sands provides a good working mix for repair of 1/8" - 1-1/2" in depth. Primary features:

- Single component, mixes with water.
- Approximately 18-24 SF coverage at 1/4".

21-10465 40 lb. Bag

Spec Sheet MSDS/SDS

SPEC CHEM SPEC PRIME

A ready-to-use, re-wettable primer that bonds Spec Flow Underlayment to horizontal concrete. Recommended for interior and dry applications only. Primary features:

- Re-emulsifiable/re-wettable.
- Excellent bonding agent.
- VOC compliant.

21-10601 1-Gal. Jug

Spec Sheet MSDS/SDS

SPEC CHEM SPEC FLOW UNDERLAYMENT

A cement based, non-shrink, self-leveling floor underlayment designed for interior use. Single component and accepts floor coverings in as little as 12-18 hours. Primary features:

- Flow time of 20 minutes at 70 degrees Fahrenheit.
- Can be feather edged.
- · Self-leveling.
- Compatible with carpet and tile.

21-10600 50 lb. Bag

Spec Sheet MSDS/SDS